



Ozone Solutions



WATERZONE SE SERIES

The clearly better ozone water disinfection system.

MULTIPLE OPTIONS AVAILABLE TO FIT YOUR SPECIFICATIONS.



FEATURES OF WATERZONE SE SERIES:

FEATURES

- Stainless Steel or painted steel enclosures
 - Enclosure protects from harsh or wash-down environments
- 10-200 grams/hour ozone production
- Generates high dissolved ozone levels
- Easy and simple installation
- Automated system
- Very efficient with excellent mass transfer of ozone
- Produces ozone from integrated Oxygen Concentrator
- Central switch starts and stops system
- Includes stainless steel tank, pump, and piping
- Compact design
- Water flow from 1-300 GPM
- Ready to use upon delivery

WATERZONE SE SYSTEMS: Standard Waterzone-SE Ozone Injection System Sizes

| Waterzone-SE Systems | Ozone Output | Ozone Dosage Rates | Max Flow Rate | Tank |
|----------------------|--------------|---------------------------------------|---------------|------------|
| Waterzone-SE-10 | 10 g/hr | 1.5 PPM @ 30 GPM – 2.9 PPM @ 15 GPM | 30 GPM | 15 Gallon |
| Waterzone-SE-20 | 20 g/hr | 2.9 PPM @ 30 GPM – 5.9 PPM @ 15 GPM | 30 GPM | 15 Gallon |
| Waterzone-SE-30 | 30 g/hr | 2.6 PPM @ 50 GPM – 5.3 PPM @ 25 GPM | 50 GPM | 25 Gallon |
| Waterzone-SE-40 | 40 g/hr | 3.5 PPM @ 50 GPM – 7.0 PPM @ 25 GPM | 50 GPM | 25 Gallon |
| Waterzone-SE-60 | 60 g/hr | 1.9 PPM @ 140 GPM – 3.8 PPM @ 70 GPM | 140 GPM | 50 Gallon |
| Waterzone-SE-80 | 80 g/hr | 2.5 PPM @ 140 GPM – 5.0 PPM @ 70 GPM | 140 GPM | 50 Gallon |
| Waterzone-SE-100 | 100 g/hr | 2.2 PPM @ 200 GPM – 4.4 PPM @ 100 GPM | 200 GPM | 100 Gallon |
| Waterzone-SE-120 | 120 g/hr | 2.6 PPM @ 200 GPM – 5.3 PPM @ 100 GPM | 200 GPM | 100 Gallon |
| Waterzone-SE-150 | 150 g/hr | 2.2 PPM @ 300 GPM – 4.4 PPM @ 150 GPM | 300 GPM | 140 Gallon |
| Waterzone-SE-200 | 200 g/hr | 2.9 PPM @ 300 GPM – 5.9 PPM @ 150 GPM | 300 GPM | 140 Gallon |

| Optional Equipment | Description |
|--------------------------------|---|
| As-500 Dissolved Ozone Monitor | Monitors and controls ozone level in the water (ppm) |
| ORP Meter | Monitors ORP level in water, will also control ozone level with indirect reading |
| Remote Ambient Ozone Monitor | Monitors ozone levels near water point of use for safety purposes |
| Ozone Destruct Unit | Destroys all undissolved ozone form the contact tank and includes water trap |
| Air Compressor | Provides compressed air for Oxygen Concentrator which eliminates the need for compressed air supply (not available for Waterzone-60 and larger) |
| 50 Hz Power | Necessary for overseas use |

* Other options and larger systems available.

** The above specifications are contingent upon near perfect conditions (transfer efficiency above 85%, water pH neutral, clean & chlorine free water, etc.)

CONTACT US FOR MORE INFORMATION



Ozone Solutions, Inc.
451 Black Forest Road • Hull, IA 51239
Tel: 1.712.439.6880 | Fax: 1.712.439.6733

Visit us on the web:
www.ozonesolutions.com

Email us: info@ozonesolutions.com • sales@ozonesolutions.com

1-YEAR WARRANTY



GUARANTEE